

OLYMPIC FOOT 30mm



MODE DE FABRICATION/ PRODUCTION METHOD	EN TOUFFE / TUFTED
FIBRE / FIBRE	Diamond Shape, 100% PP
HAUTEUR DU BRIN / PILE HEIGHT	±30mm
HAUTEUR TOTALE / TOTAL HEIGHT	±32mm
POIDS DU BRIN / PILE WEIGHT	±2 260 GR/M²
POIDS TOTAL / TOTAL WEIGHT	±3 510 GR/M²
JAUGE / GAUGE	3/8"
NOMBRE DE POINTS / STITCHES (10CM)	±21
DENSITE – NOMBRE DE POINTS / STITCHES (M²)	±21 000
DTEX	16 500
SUPPORT	Latex, PP cloth et non woven fabric
PERMEABILITE / WATER PERMEABILITY	±60 L/MIN/M²
STABILITE UV / UV STABILITY	DIN 53387 STANDARD (6 000 HEURES)
LARGEUR DES ROULEAUX / ROLL WIDTH (M)	2 M / 4 M
LONGUEUR DES ROULEAUX / ROLL LENGTH (M)	±25 M
RESISTANCE A L'ARRACHEMENT	>30 NEWTONS
RESISTANCE A LA LUMIERE (ECHELLE DE BLEUS 1-8)	>7 DIN 54004
RESISTANCE DES COULEURS (ECHELLE DE GRIS 1-5)	>4 DIN STANDARD
FABRIQUE EN	BELGIQUE
GARANTIE	8 ANS